

LABELMATE LLC

“Quick-Chucks”™

Quick-locking Core Chucks



Some of the Quick-Chuck Family

Remove all parts from shipping container and verify contents.

- Single Lock-Knob operation
- 10-different Models available
- Ideal for Slitting or Volume Label Production

Package Contents

- “Quick-Chuck” Core Chuck size as ordered
- Allen Wrench
- Inner Flange
- Optional Outer Flange if ordered

Retain the Shipping Container and Packaging for Storage and Transport.

• **KEEP MANUAL IN A SAFE PLACE FOR FUTURE REFERENCE** •

Product Limited Warranty

All Labelmate Products are warranted to the original end-user customer to be free from defects in materials and workmanship. If it is determined by Labelmate that a product has failed under the terms of this warranty, the product will be repaired or replaced at no charge to the customer. Labelmate reserves all rights to determination of coverage and liability under this warranty. The warranty period for all new Labelmate products is outlined below:

Warranty Period	Products Covered
5 years	Label Reminders Label Unwinders
3 years	Quick-Chucks Label Counters & Slitters (mechanical parts only) Label Dispensers Printer Mechanisms
1 year	Power Supply Modules Counter Modules Encoders Any products not specified above.

The warranty period for all products starts on the date purchased by the original end-user customer. Warranty coverage is not transferable with ownership and will terminate immediately upon rental, resale or any other change in ownership. This warranty does not cover repair to any product which is damaged, has been modified, is missing parts, or has been opened or repaired by any unauthorized person. Use of any unauthorized accessory or attachment will void coverage. Purchase documentation should be retained for coverage verification.

In the event your product requires service, please contact Labelmate at (877) 833-7149 toll-free inside the USA or +1 (702) 435-8535 outside the USA, for the location of the nearest authorized service center or questions regarding warranty coverage. The customer assumes responsibility for all cost and risk incurred in transport for service.

Labelmate makes no other warranty of any kind expressed or implied, or to suitability or fitness for a particular purpose. No other person, agent or reseller is authorized to give any warranties on behalf of Labelmate. Any obligation to warranty other than that specifically addressed above is hereby disclaimed.

LABELMATE LLC

12A Sunset Way, Henderson, NV 89014 USA
(702) 435-8535 FAX (702) 435-8536
Toll-Free (877) 833-7149 in USA!
info@labelmate.com

LABELMATE EUROPE
Brussels, Belgium

www.labelmate.com



WARNING

This product is for indoor use only.
Not for use in wet locations.



SET-UP

Secure a Plastic Label Flange to the back of the “Quick-Chuck” with a Phillips screwdriver. Mount the “Quick-Chuck” onto the shaft of the Rewinder or Unwinder securing it with the Allen wrench provided.

USE

To use a “Quick-Chuck”, just slide your label roll over the “Quick-Chuck” and turn the convenient lock knob. Instantly your roll is locked in place.

The Optional Outer Flange may be used if desired.

To remove the roll, just give the lock knob a turn to the left and pull your roll off the machine.

LABELMATE’s “Quick-Chucks” are available in 10 models to accept popular core sizes. “Quick-Chucks” fit LABELMATE Models CAT-2, CAT-40G, UCAT-1, UCAT-2, UCAT-40 or any 0.625” dia. Shaft with a flat. Other shaft sizes are available for OEMs. The UCAT-40 16-inch Powered Unwinder comes equipped with a C-76-170 “Quick-Chuck” for standard 3-inch cores.

MAINTENANCE:

Quick-Chucks require no maintenance.

SPECIFICATIONS:

Roll Weight: Maximum 44-lbs. (20Kg).

Shaft Diameter: Fits 0.625” diameter shaft with flat. Other sizes are available for OEM quantity applications.

Key to Model Numbers = C - [DIAMETER] – [WIDTH]

MODEL	DIAMETER	WIDTH
C-1.5-170	38.1-mm / 1.5”	170-mm (6.5 inches)
C-1.5-270	38.1-mm / 1.5”	270-mm (10.6 inches)
C-40-170	40-mm / 1.575”	170-mm (6.5 inches)
C-70-170	70-mm / 2.756”	170-mm (6.5 inches)
C-76-170	76-mm / 3”	170-mm (6.5 inches)
C-76-220	76-mm / 3”	220-mm (8.6 inches)
C-76-270	76-mm / 3”	270-mm (10.6 inches)
C-100-170	100-mm / 4”	170-mm (6.5 inches)
C-100-220	100-mm / 4”	220-mm (8.6 inches)
C-100-270	100-mm / 4”	270-mm (10.6 inches)