



RRC-300-U Universal Reel-to-Reel Counting System

The new RRC-300-U Universal Reel-to-Reel Counting System uses a state of the art ultrasonic fork detector that allows the RRC-300-U to count almost any type of labels, including transparent or dark labels. The ultrasonic detector detects the labels by sensing the difference in thickness between the backing paper and the backing paper plus label.

The RRC-300-U accepts roll with a maximum outer diameter of 300mm for the standard version and 330mm for the ACH version. Take-up core is available both in Standard and Adjustable Core Holder.

The Standard take-up shaft is available is 38, 40, 44, 70 and 76mm. The ACH (Adjustable Core Holder) accepts cores from 25 to 101mm. The supply core is supplied in both 40mm and 76mm (other core diameters available on-demand).

Designed for all-day, every-day use, the **RRC-300-U Universal Reel-to-Reel Counting System** are backed by LABELMATE's famous 3-Year Parts and Labor Limited Warranty, assuring you trouble-free performance.



RRC-300-U

MODEL	ADD SUFFIX	DESCRIPTION	LABEL WIDTH (mm)	ROLL DIAM. (mm)	SPEED
RRC-300-U	STANDARD	Self-contained Counter System with 90-250VAC, 50-60Hz, 60VA Universal Power Supply. 40 & 76mm for the supply core and take-up shaft, (other diameters on demand).	152	300	72cm/sec. ¹ 235cm/sec. ²
	ACH	Self-contained Counter System with 90-250VAC, 50-60Hz, 60VA Universal Power Supply. 40 & 76mm for the supply core. Adjustable Core Holder (25mm to 101mm) for the take-up shaft.	152	330	72cm/sec. ¹ 235cm/sec. ²

¹ Maximum speed with a 76mm take-up roll diameter.

² Maximum speed at end of 300mm roll.

Specifications are subject to change without notice. DataRRC-300-U_Eur 09/2011